

LINE REMOVER

For low cost, fast efficient line removal

- Line removal permanently!
- Up to 150mm wide line removal.
- Easy to use Works in traffic, compact design suitable for concrete or asphalt.
- Centrifugal clutch Easier starting. Enables engine to idle with cutter head resting on roadway, without machine moving forward.
- Works fast
- Self-propelling
- Revolutionary Line Remover Head Assembly mounted between twin heavy-duty bearings, comprising five individual cutter shafts.
 Components heat-treated for longer life.





Cutter Head Assembly

- Hardened steel cutters shear off paint with high speed cutting action. Cutters are spaced on five shafts for 4" or 6" line removal.
- On the job cutter change takes only minutes.

Robust Construction

• Frame is heavy section welded steel plate, reinforced at stress points, while cutter head assembly cover lid is 10 gauge steel plate.

Operator

• Protected by steel plate mounted at rear of cutter head assembly.

Handle

• Wide bar with rubber grips ensure good control. Throttle control and cut-out switch mounted adjacent to handle bar.

Vee Belt Drive

• Guarded twin vee belts drive cutter assembly

THE EQUIPMENT YOU NEED – THE SERVICE YOU EXPECT



SPECIFICATION	
Width of removed line	25mm - 150mm
Dimensions	1220mm L x 650mm W x 920mm H
Weight	99kg
Engine	13 HP 2:1 Reduction Johno + Jono Pull Start

A1 Roadlines Pty Ltd

89 Rushdale Street Knoxfield, Victoria 3180

P: 1300 217 623 (A1ROAD)E: sales@a1roadlines.com.au

www.a1roadlines.com.au